

# Product datasheet

Specifications



## Network Power supply with battery backup, 12Vdc, 1A, CEE7, lithium battery

CP12010LI-GR

### Overview

Lead time Usually in Stock

### Main

|                     |                         |
|---------------------|-------------------------|
| Main Input Voltage  | 220 V<br>230 V<br>240 V |
| Main Output Voltage | 12 V DC                 |
| Rated power in W    | 12 W                    |
| Rated power in VA   | 12 VA                   |
| Battery type        | Li-Ion (Lithium-Ion)    |

### Physical

|                     |                    |
|---------------------|--------------------|
| Height              | 7.8 cm             |
| Width               | 4.8 cm             |
| Depth               | 7.6 cm             |
| Net weight          | 0.2 kg             |
| Mounting preference | No preference      |
| Mounting mode       | Not rack-mountable |
| Two post mountable  | 0                  |
| USB compatible      | No                 |

### Output

|                                 |      |
|---------------------------------|------|
| Maximum configurable power in W | 12 W |
|---------------------------------|------|

### Conformance

|           |                      |
|-----------|----------------------|
| Standards | EN 55024<br>EN 60950 |
|-----------|----------------------|

### Environmental

|                                       |           |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity                     | 5...95 %  |

---

|                                     |             |
|-------------------------------------|-------------|
| Ambient air temperature for storage | -15...60 °C |
|-------------------------------------|-------------|

## Batteries & Runtime

---

|                                |   |
|--------------------------------|---|
| Number of battery filled slots | 0 |
|--------------------------------|---|

---

|                              |   |
|------------------------------|---|
| Number of battery free slots | 0 |
|------------------------------|---|

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

---

|                  |         |
|------------------|---------|
| Package 1 Height | 11.3 cm |
|------------------|---------|

---

|                 |        |
|-----------------|--------|
| Package 1 Width | 9.9 cm |
|-----------------|--------|

---

|                  |        |
|------------------|--------|
| Package 1 Length | 5.2 cm |
|------------------|--------|

---

|                  |         |
|------------------|---------|
| Package 1 Weight | 0.28 kg |
|------------------|---------|

---

|       |                |
|-------|----------------|
| SCC14 | 10731304344091 |
|-------|----------------|

## Offer Sustainability

---

|                   |  |
|-------------------|--|
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
|-------------------|--|

## Contractual warranty

---

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)