

Product datasheet

Specifications

APC Easy UPS On-Line SRV 1000VA RM 230V with Rail Kit



SRV1KRIRK

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	800 W
Rated power in VA	1000 VA
Plug standard	IEC 60320 C14
Output connection type	3 IEC 60320 C13
Number of rack unit	2U
Cable length	1.50 m
Number of cables	1
Provided equipment	1 IEC 60320 C13 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable 1 rack mounting brackets 1 rack mounting support rails user manual Basic UPS signalling RS-232 cable USB cable CD with software User manual IEC-C14 - Shuko input power cord C13-C14 power cord Rack mounting brackets Rack mounting support rails

General

Max runtime	4 min
Number of power module filled slots	0

Number of power module free slots	0
-----------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Black (RAL 7010)
--------	------------------

Height	8.6 cm
--------	--------

Width	43.7 cm
-------	---------

Depth	31.2 cm
-------	---------

Net weight	11 kg
------------	-------

Mounting location	Front
-------------------	-------

Mounting preference	Lower
---------------------	-------

Mounting mode	Rack-mounted
---------------	--------------

USB compatible	Yes
----------------	-----

Mounting position	Horizontal
-------------------	------------

Input

Input voltage limits	110...285 V half load 160...280 V full load
----------------------	--

Network frequency	40...70 Hz auto sensing
-------------------	-------------------------

Output

Maximum configurable power in VA	1000 VA
----------------------------------	---------

Maximum configurable power in W	800 W
---------------------------------	-------

Output frequency	50/60 Hz +/- 1 Hz sync to mains
------------------	---------------------------------

Harmonic distortion	3 %
---------------------	-----

UPS type	Double conversion online
----------	--------------------------

Wave type	Sine wave
-----------	-----------

Efficiency	88 % (full load)
------------	------------------

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

Bypass type	Internal bypass (automatic and manual)
-------------	--

Crest factor	3 : 1
--------------	-------

Conformance

Product certifications	CE UKCA EAC TISI
------------------------	---------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental


Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...3000 m
--------------------	------------

Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	372 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery life	3...5 year(s)
Replacement battery	APCRBCV200 
Battery charger power	30 W rated

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	55 cm
Number of Units in Package 1	1
Package 1 Width	70 cm
Package 1 Height	21.8 cm
Package 1 Weight	13.1 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------