

Product datasheet

Specifications



APC Easy UPS BVX 1600VA, 230V, AVR, Schuko Sockets

BVX1600LI-GR

Overview

Lead time Usually in Stock

Main

Input voltage 230 V AC 1 phase

Output voltage 230 V AC 1 phase

Rated power in W 900 W

Rated power in VA 1600 VA

Plug standard Schuko

Nb of power socket outlets 4 Schuko

Cable length 1.22 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment User manual

General

Max runtime 240 min

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

UPS size WS

Physical

Colour Black

Height 19 cm

Width 14 cm

Depth 39 cm

Net weight 10.2 kg

Mounting support Floor

Mounting preference No preference

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.56

Output

Maximum configurable power in W	900 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 900 W
Graph display	1
Half load runtime	00:06:30 450 W
Maximum configurable power in VA	1600 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	7.0 Ah
Battery life	2...3 year(s)
Replacement battery	APCRBC176 

Extended runtime	0
------------------	---

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Package 1 Weight	11.2 kg
Package 1 Height	29.7 cm
Package 1 Width	23.5 cm
Package 1 Length	49.5 cm
SCC14	10731304404610

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
