



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Output voltage	230 V
Rated power in W	500 W
Rated power in VA	1000 VA
Input Connection Type	Schuko CEE 7/7P
Cable length	1.00 M
Provided equipment	User manual

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

Colour	Black
Height	11.9 Cm
Width	9.5 Cm
Depth	18 Cm
Net weight	1.6 Kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50 Hz
Input voltage limits	184...284 V

Output

Maximum configurable power in W	500 W
---------------------------------	-------

Conformance

Product certifications	EAC
------------------------	-----

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...90 %
Storage altitude	0.00...1015.90 M

Surge Protection and Filtering

Surge energy rate	148 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.8 Cm
Package 1 Width	12.5 Cm
Package 1 Length	9.8 Cm
Package 1 Weight	1.36 Kg
SCC14	10731304341823

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**