

Product datasheet

Specifications



APC Smart-UPS C, Line Interactive, 2000VA, Tower, 230V, 6x IEC C13+1x IEC C19 outlets, USB and Serial communication, AVR, Graphic LCD

SMC2000I

Overview

| | |
|---------------------|---|
| Presentation | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
| Lead time | Usually Ships within 2 Weeks |

Main

| | |
|-------------------------------|---|
| Main Input Voltage | 230 V |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 230 V |
| Rated power in W | 1300 W |
| Rated power in VA | 2000 VA |
| Input Connection Type | IEC 320 C20 |
| Output connection type | 6 IEC 320 C13 1 IEC 320 C19 |
| Number of rack unit | 0U |
| Battery type | Lead-acid battery |
| Provided equipment | CD with software Documentation CD USB cable |

General

| | |
|--|-------------|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Product web sub-family | Entry level |
| Redundant | No |

Physical

| | |
|---------------|---------|
| Colour | Black |
| Height | 21.6 cm |
| Width | 17 cm |
| Depth | 44 cm |

| | |
|----------------------------|--------------------|
| Net weight | 27.5 kg |
| Mounting location | Front |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | Yes |

Input

| | |
|-----------------------------|---------------------------------------|
| Input voltage limits | 170...300 V adjustable 180...287 V |
| Network frequency | 47...63 Hz |

Output

| | |
|---|----------------------------|
| Harmonic distortion | Less than 5 % at full load |
| Maximum configurable power in VA | 2000 VA |
| Maximum configurable power in W | 1300 W |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Output frequency | 50 Hz sync to mains |

Conformance

| | |
|-------------------------------|--|
| Product certifications | C-Tick CE EAC GOST SABS VDE |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|--|-------------------|
| Acoustic level | 45 dBA |
| Heat dissipation | 135 Btu/h |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0.00...15240.00 m |
| Relative humidity | 0...95 % |
| Storage Relative Humidity | 0...95 % |

Batteries & Runtime

| | |
|---------------------------------------|-----|
| Extended runtime | 0 |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |

| | |
|--|---|
| Number of battery replacement quantity | 1 |
| Battery life | 3...5 year(s) |
| Replacement battery | APCRBC148  |
| Battery power in VAH | 499 VAh runtime |
| Battery charger power | 166 W rated |

Communications & Management

| | |
|---------------|---|
| Control panel | Multifunction LCD status and control console |
| Free slots | 0 |
| Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|-------------------|--|
| Surge energy rate | 300 J |
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 33 cm |
| Package 1 Width | 59 cm |
| Package 1 Length | 37 cm |
| Package 1 Weight | 30 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)