

Product datasheet

Specifications



APC Essential SurgeArrest 5 Outlet 2 USB Ports Black 230V Germany

PME5U2B-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage	220 V 230 V 240 V
Input Connection Type	Schuko CEE 7/7P
Cable length	1.52 m
Number of cables	1
Provided equipment	User manual

Physical

Colour	Black
Height	4 cm
Width	33.5 cm
Depth	6.3 cm
Net weight	0.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Input power	2300 W
Network frequency	50/60 Hz
Switching current capacity	10 A

Output

Number of power socket outlets	5
Outlet standard	Schuko CEE 7

Conformance

Product certifications	CE
------------------------	----

Marking	CE Mark
---------	---------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	45 dB
Peak current	15 kA normal mode
Surge energy rate	680 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	12 cm
Package 1 Length	36.5 cm
Package 1 Weight	0.607 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	27.5 cm
Package 2 Width	30 cm
Package 2 Length	39 cm
Package 2 Weight	7.84 kg
SCC14	10731304347054

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)