

# Product datasheet

Specifications



## APC Back-UPS, 1600VA, Tower, 230V, 4x CEE 7/7 Schuko outlets, AVR

BX1600MI-GR

### Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	Schuko CEE 7/7P
Cos phi	0.56
Input voltage limits	140...300 V
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Rated power in W	900 W
Rated power in VA	1600 VA
Output connection type	4 Schuko
USB Charging Port	None
Maximum configurable power in VA	1600 VA
Maximum configurable power in W	900 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 900 W
Half load runtime	00:06:30 450 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains

### Graphs

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>

### Complementary

Battery capacity	7.0 Ah
Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
UPS connectivity	None
Surge energy rate	273 J
Cable length	1.2 m
Number of cables	1
Colour	Black

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	190 mm
Width	140 mm
Depth	390 mm
Product weight	10.3 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Back-UPS
Product or component type	Uninterruptible power supply (UPS)

## Environment

Product certifications	CE CB EAC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	40 dBA
Operating altitude	0...3000 m

## Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery life	3...5 year(s)

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	29.7 cm
<b>Package 1 Width</b>	49.5 cm
<b>Package 1 Length</b>	23.5 cm
<b>Package 1 Weight</b>	11.3 kg
<b>SCC14</b>	10731304410871

## **Contractual warranty**

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	403 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	108 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	292 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	Ec96232c-7000-4722-846e-a372cdfca8dc
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture


Recyclability potential, in %	62
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

